

### Swing Gate Wall Mounted Equipment Rack 19" Panel Mount, SB708 Series

- Wall mounted rack hinges to either side providing convenient access to the back of mounted equipment
- Easy, one person installation in about five minutes
- Mounting holes on 16" centers
- Door can be completely removed from frame after installation
- EIA-310-D compliant with universal 5/8" (16mm), 5/8" (16mm), 1/2" (13mm) mounting spacing
- #12-24 tapped mounting rails
- Available in EIA widths 19" and 23"
- Available in mounting heights of 13 RMU, 21 RMU, 27 RMU and 41 RMU
- Available in depths of 8", 12" and 18"
- Packaged unassembled in protective carton suitable for parcel shipment
- Constructed of a steel frame with aluminum door
- Integrated cable tie/cable wrap tie-down points
- Load rating: 150 lbs. (assumes suitable mounting surface)
- UL 1863 listing pending
- Available in flat black (FB), telco gray (TG), silver powder (SL) or computer white (CW) finishes.



SB 708	(Width)	(Height)	(Depth)
			08 = 8"
			12 = 12"
			18 = 18"
		30 = 29.12	(13 RMU's)
		44 = 43.12	(21 RMU's)
		54 = 53.62	(27 RMU's)
		79 = 78.12	(41 RMU's)
	19 = 19.31"		(19 EIA PNL)
	23 = 23.31"		(23 EIA PNL)

### Technical Information

Materials	
Overall Construction	14 gauge steel backplate and top angle bracket 11 gauge steel bottom angle bracket 5052-H32 aluminum door frame with black polycarbonate plastic hinges
Height	Overall heights include 30" (635mm), 44" (990mm), 54" (1270mm) and 79" (1879mm)
Depth	Overall depths include 8" (203mm), 12" (305mm) and 18" (457mm)
Width	Mounting widths include 19" (482mm) and 23" (584mm) EIA mounting spacing
Finish	
Flat Black	Powder coat, flat finish
Computer White	Powder coat, flat finish
Silver Powder Cost	Powder coat, flat finish
Telco Gray	Powder coat, flat finish
Approvals and Certifications	
EIA	Mounting hole pattern compliant to EIA-310-D
UL	UL 1863 listing pending
Shipping	
Shipping Weight (lbs)	Part Number    Lbs.    Box Height    Box Width    Box Depth
	SB708193008    30    31.25"    20.75"    4.75"
	SB708193012    32    31.25"    20.75"    4.75"
	SB708193018    35    31.25"    20.75"    4.75"
	SB708194408    32    45.25"    20.75"    4.75"
	SB708194412    34    45.25"    20.75"    4.75"
	SB708194418    38    45.25"    20.75"    4.75"
	SB708195408    34    56.0"    20.75"    4.75"
	SB708195412    37    56.0"    20.75"    4.75"
	SB708195418    40    56.0"    20.75"    4.75"
	SB708197908    39    80.25"    20.75"    4.75"
	SB708197912    41    80.25"    20.75"    4.75"
	SB708197918    45    80.25"    20.75"    4.75"
Packaging	Individually packaged in protective cardboard carton suitable for parcel shipment

## Specification Example (available choices are shown between the [ ])

Wall mounted swing gate network communications equipment racks shall support [19", 23"] rackmount network equipment including switches, patch panels and equipment shelves. The rack shall be compliant to the requirements of EIA-310-D and be UL listed as a communications circuit accessory per the UL 1863 standard. The rack shall be [30" (635mm) , 44" (990mm) , 54" (1270mm) , 79" (1879mm)] in overall height containing [13, 21, 27, 41] 1.75" rack mount units spaces for mounting equipment. Mounting holes shall be tapped #12-24 threaded holes and arranged in the 5/8"-5/8"-1/2" (16mm-16mm-13mm) universal hole pattern. The rack shall have a load rating not less than 150 lbs. (68 kg) when the load is evenly distributed. The rack shall be designed to allow opening of the door up to 130 degrees to the left or the right. The rack shall be provided with a [flat black powder coat, telco gray power coat, computer white powder coat, silver powder coat] finish.

## Part Numbers

Description	Finish	Part Number	Material Number
Wall mounted swing gate rack, 19"W x 30"H (13 RMU) x 8"D	Flat Black	SB708193008FB	11740231
<b>Wall mounted swing gate rack, 19"W x 30"H (13 RMU) x 12"D</b>	<b>Flat Black</b>	<b>SB708193012FB</b>	<b>11740235</b>
<b>Wall mounted swing gate rack, 19"W x 30"H (13 RMU) x 18"D</b>	<b>Flat Black</b>	<b>SB708193018FB</b>	<b>11726518</b>
Wall mounted swing gate rack, 19"W x 44"H (21 RMU) x 8"D	Flat Black	SB708194408FB	11740263
Wall mounted swing gate rack, 19"W x 44"H (21 RMU) x 12"D	Flat Black	SB708194412FB	11740291
<b>Wall mounted swing gate rack, 19"W x 44"H (21 RMU) x 18"D</b>	<b>Flat Black</b>	<b>SB708194418FB</b>	<b>11726522</b>
Wall mounted swing gate rack, 19"W x 54"H (27 RMU) x 8"D	Flat Black	SB708195408FB	11740317
Wall mounted swing gate rack, 19"W x 54"H (27 RMU) x 12"D	Flat Black	SB708195412FB	11740340
<b>Wall mounted swing gate rack, 19"W x 54"H (27 RMU) x 18"D</b>	<b>Flat Black</b>	<b>SB708195418FB</b>	<b>11726523</b>
Wall mounted swing gate rack, 19"W x 79"H (41 RMU) x 8"D	Flat Black	SB708197908FB	11740456
Wall mounted swing gate rack, 19"W x 79"H (41 RMU) x 12"D	Flat Black	SB708197912FB	11740464
Wall mounted swing gate rack, 19"W x 79"H (41 RMU) x 18"D	Flat Black	SB708197918FB	11740472

\***BOLD** indicates popular item that is always stocked

## Cross Reference

Cooper B-Line's SB708 series wall mounted swing gate racks are similar in form, fit and function to the following parts made by other manufacturers –

Part Number	Material Number	CPI	Hoffman	Homaco
SB708193012FB	11740235	11790-712 or 13602-712	N/A	19-21-T12DB
SB708193018FB	11726518	11790-718 or 13602-718	E19SWM12U20	19-21-T18DB
SB708194418FB	11726522	11791-718 or 13604-718	E19SWM20U20	19-35-T18DB
SB708195418FB	11726523	11807-718 or 13608-718	E19SWM25U20	19-48-T18DB

Specification subject to change without notice. For further information, please contact –

Cooper B-Line - USA • 509 West Monroe Street • Highland, IL 62249 • United States  
 Phone: (800) 851-7415 • Fax: (800) 356-1438 • Email: [blineus@cooperbline.com](mailto:blineus@cooperbline.com)