

Sub-unit	FIBER CHART:		
	MTP		LC Uniboot
1	BLUE	1-1	1-B
	ORANGE	1-2	1-A
	GREEN	1-3	2-B
	BROWN	1-4	2-A
	GREY	1-5	3-B
	WHITE	1-6	3-A
	RED	1-7	4-B
	BLACK	1-8	4-A
	YELLOW	1-9	5-B
	VIOLET	1-10	5-A
	ROSE	1-11	6-B
	AQUA	1-12	6-A
2	BLUE	2-1	7-B
	ORANGE	2-2	7-A
	GREEN	2-3	8-B
	BROWN	2-4	8-A
	GREY	2-5	9-B
	WHITE	2-6	9-A
	RED	2-7	10-B
	BLACK	2-8	10-A
	YELLOW	2-9	11-B
	VIOLET	2-10	11-A
	ROSE	2-11	12-B
	AQUA	2-12	12-A

LENGTH TOLERANCE:


LENGTH (L)	TOLERANCE
$\leq 3M$	+150MM/-0
$30M \geq L > 3M$	+300MM/-0
$> 30M$	+1%/-0

LC SPECIFICATIONS:

Fiber Type	TUBE JACKET COLORS	Max. Insertion Loss	Min. Return Loss
50/125	Orange	0.3dB	25dB
62.5/125	Orange		30dB
10 GIG(50/125)	Aqua	0.3dB	30dB
SM	Yellow		55dB

MTP SPECIFICATIONS:

Fiber Type	TUBE JACKET COLORS	Max. Insertion Loss	Min. Return Loss
50/125	Orange	0.75dB	20dB
62.5/125	Orange		25dB
10 GIG(50/125)	Aqua	0.5dB	50dB
SM	Yellow		50dB

 Tolerances unless otherwise specified	Designed By	2007/05/18	Title	24 Fiber MTP-LC UNIBOOT
	Checked By			Drawing No
000667-18052007	Approved By		<b>Lynn Electronics corp.</b>	
Scale				
Version	1.0	sheet 1 of 1		